PORSCHE

Macan 4S





PORSCHE









Svarbi informacija

Rodomas vaizdas gali skirtis nuo realaus automobilio vaizdo.

PORSCHE

Techniniai duomenys

Macan 4S

1 pavaros automatinė transmisija

Variklis

Elektrinio motoro sukimo momentas	560 Nm
Galia iki (kW)	330 kW
Galia iki (AG)	449 PS
Padidinta galia su „Launch Control" iki (kW)	380 kW
Padidinta galia su „Launch Control" iki (AG)	516 PS
Didžiausias sukimo momentas (Nm)	785 Nm
Didžiausias sukimo momentas (Nm) su sistema „Launch Control"	820 Nm

Charakteristikos

Maksimalus greitis	240 km/h
Įsibėgėjimas 0 - 100 km/h su sistema „Launch Control"	4,1 s
Įsibėgėjimas 0 - 160 km/h su sistema „Launch Control"	9,1 s
Įsibėgėjimas 0 - 200 km/h su sistema „Launch Control"	14,3 s
Įsibėgėjimas (80-120km/h) (50-75 mph)	2,4 s

Nuvažiuojamas atstumas

Vidutinis nuvažiuojamas atstumas (konkretaus automobilio)	561 km
Vidutinis nuvažiuojamas atstumas (modelio)	523 - 612 km
Nuvažiuojamas atstumas mieste (konkretaus automobilio)	716 km
Nuvažiuojamas atstumas mieste (modelio)	667 - 778 km

PORSCHE

Krovimas

Bendroji akumuliatoriaus talpa	100 kWh
Maksimali nuolatinės srovės krovimo galia	270 kW
Kintamosios srovės (AC) įkrovimo laikas, naudojant 9,6 kW (nuo 0 iki 100 proc.)	11,5 h
Kintamosios srovės (AC) įkrovimo laikas, naudojant 11 kW (nuo 0 iki 100 proc.)	10 h
Kintamosios srovės (AC) įkrovimo laikas, naudojant 19,2 kW (nuo 0 iki 100 proc.)	5,8 h
Kintamosios srovės (AC) įkrovimo laikas, naudojant 22 kW (nuo 0 iki 100 proc.)	5,3 h
Nuolatinės srovės (DC) įkrovimo laikas, naudojant 400V technologiją (nuo 10 iki 80 proc.)	33 min.
Nuolatinės srovės (DC) įkrovimo laikas, naudojant maksimalią nuolatinės srovės krovimo galią (nuo 10 iki 80 proc.)	21 min
Nuvažiuojamas atstumas (WLTP) su 10 min. 150 kW įkrova	123 km
Nuvažiuojamas atstumas (WLTP) su 10 min. didžiausia DC įkrovimo galia	214 - 250 km

Kuro sąnaudos/ emisija (WLTP)

Vidutinės elektros sąnaudos (WLTP) (konkretaus automobilio)	19,3 kWh/100 km
Vidutinės elektros sąnaudos (WLTP) (modelio)	20,5 - 17,7 kWh/100km
Elektros sąnaudos mieste (WLTP) (modelio)	16 - 13,8 kWh/100km
Mažos elektros sąnaudos (WLTP) (konkretaus automobilio)	14,5 kWh/100 km
Mažos elektros sąnaudos (WLTP) (modelio)	15,4 - 13,3 kWh/100km
Vidutiniškos elektros sąnaudos (WLTP) (konkretaus automobilio)	15,4 kWh/100 km
Vidutiniškos elektros sąnaudos (WLTP) (modelio)	16,4 - 14,2 kWh/100km
Didelės elektros sąnaudos (WLTP) (konkretaus automobilio)	17,7 kWh/100 km
Didelės elektros sąnaudos (WLTP) (modelio)	18,8 - 16,2 kWh/100km
Itin didelės elektros sąnaudos (WLTP) (konkretaus automobilio)	24,7 kWh/100 km
Itin didelės elektros sąnaudos (WLTP) (modelio)	26,3 - 22,7 kWh/100km
Vidutinės CO_2 emisijos (WLTP) (konkretaus automobilio)	0 g/km
Vidutinės CO_2 emisijos (WLTP) (modelio)	0 - 0 g/km

Triukšmingumo lygis (patvirtinta pagal UN-R 51)

Pravažiuojančio automobilio triukšmo lygis	69 dB(A)

PORSCHE

Kėbulas

Ilgis	4 784 mm
Plotis	1 938 mm
Plotis (su veidrodėliais)	2 152 mm
Plotis (su užlenktais veidrodėliais)	1 954 mm
Aukštis (standartinė pakaba su PASM sistema)	1 624 mm
Aukštis (standartinė pakaba su PASM sistema ir stogo bagažinės bėgeliais)	1 633 mm
Aukštis (pneumatinė pakaba, standartinis lygis) (EC)	1 623 mm
Aukštis (pneumatinė pakaba, standartinis lygis su stogo bagažinės bėgeliais) (EC)	1 632 mm
Aukštis (pneumatinė pakaba, bekelės (Off-Road) lygis)	1 643 mm
Aukštis (pneumatinė pakaba, bekelės (Off-Road) lygis su stogo bagažinės bėgeliais)	1 652 mm
Aukštis (pneumatinė pakaba, bekelės (Off-Road) lygis)	1 663 mm
Aukštis (pneumatinė pakaba, bekelės (Off-Road) lygis su stogo bagažinės bėgeliais)	1 672 mm
Aukštis (pneumatinė pakaba, žemiausias lygis)	1 608 mm
Aukštis (pneumatinė pakaba, žemiausias lygis su stogo bagažinės bėgeliais)	1 617 mm
Aukštis (pneumatinė pakaba, žemiausias lygis)	1 593 mm
Ratų bazė	2 893 mm
Apsisukimo spindulys	12,1 m
Tuščios transporto priemonės svoris	2 345 kg
Tuščios transporto priemonės svoris (EU)	2 420 kg
Didžiausias leistinas svoris	2 930 kg
Leistina apkrova	585 kg
Maksimali tempimo kablio apkrova (EG)	100 kg
Maksimali transporto priemonės vilkimo apkrova	2 500 kg
Maksimali transporto priemonės vilkimo apkrova (unbraked)	750 kg
Leistina maksimali stogo apkrova su Porsche stogo transportavimo sistema	75 kg

PORSCHE

Pravažumas

Max prošvaisa (tarp žemės ir vandeniui jautrių dalių, standartinė pakaba)	300 mm
Max.prošvaisa (standartinė pakaba su PASM sistema)	186 mm
Max prošvaisa (tarp žemės ir vandeniui jautrių dalių, standartinė pakaba su PASM)	300 mm
Nuožulnios plokštumos įveikimo kampas (standartinė pakaba su PASM sistema)	15 °
Nuokalnės kampas (standartinė pakaba su PASM sistema)	20,8 °
Max prošvaisa (tarp žemės ir vandeniui jautrių dalių, standartinė pakaba) (EC)	300 mm
Max prošvaisa (standartiniu režimu)	300 mm
Max prošvaisa (pneumatinė pakaba, bekelės (Off-Road) lygis)	205 mm
Max prošvaisa (tarp žemės ir vandeniui jautrių dalių, pneumatinė pakaba, bekelės (Off-Road) lygis)	320 mm
Nuožulnios plokštumos įveikimo kampas (pneumatinė pakaba, bekelės (Off-Road) lygis)	16,6 °
Max prošvaisa (pneumatinė pakaba, bekelės važiavimo aukštis)	225 mm
Max prošvaisa (bekelės režimu)	340 mm
Nuožulnios plokštumos įveikimo kampas (pneumatinė pakaba)	18,2 °
Max prošvaisa (pneumatinė pakaba, pažemintu rėžimu)	170 mm
Nuožulnios plokštumos įveikimo kampas (pneumatinė pakaba, pažemintu rėžimu)	13,7 °

Talpa

Bagažo skyriaus tūris, priekyje	84 l
Bagažo skyriaus talpa	518 l
Bagažo skyrius (su atlenktomis sėdynėmis)	1 288 l

Kuro ir CO2 duomenys pagal ES direktyvą (EG) 715/2007: Duomenys nenurodo konkrečios transporto priemonės ir nėra pasiūlymo dalis, tačiau naudojami tik skirtingų transporto priemonių palyginimui. Dėl papildomų opcijų ir kitų priedų (pvz. kaip padangos, oro kondicionieriai, stogo bagažinės) gali atsirasti nukrypimų nuo nurodyto degalų sąnaudų ir išmetamo CO2 kiekio.

Standartinė įranga

Macan 4S

Ratlankiai

- 20 colių „Macan S" ratlankiai Set of alloy wheels with Lightweight Aero Design painted in Black (high-gloss) with highly polished front surfaces

  Front axle: 7.5 J x 20 ET 32 with tyres 235/55 R20
  Rear axle: 10 J x 20 ET 49 with tyres 285/45 R20

Dažyti ratlankiai

- Centriniai ratlankių dangteliai su nespalvota „Porsche" emblema

Padangos

- 20 colių vasarinės padangos Summer tyres to replace the standard all-season tyres that come with 20-inch wheels

Ratlankių aksesuarai

- Nuo vagystės apsaugantys ratų varžtai
  Apsaugos nuo vagystės komplektą sudaro keturi koduoti ratų varžtai (po vieną kiekvienam ratui) ir vienas adapteris. Ratų varžtai turi varžto galvutę su specialios formos vidiniu profiliu ir gali būti atsukti tik naudojant komplekte esantį adapterį.
- Padangų slėgio stebėjimo sistema (TPM)

Sėdynės

- 8 padėčių, elektra valdomos, komfortiškos priekinės sėdynės
  Electric adjustment of:- seat height- fore-aft position- seat angle- backrest angle
  Headrests can be manually adjusted horizontally.
  Storage of personalised settings for driver seat and exterior mirror positions.
- 4+1 sėdynės
  - Split-folding rear bench seat (40 : 20 : 40) and folding centre armrest with cupholder- Seat occupancy detection for all rear seats- Mechanical remote backrest unlocking- Cargo position of the rear seat system (2 backrest positions)
- Šildomos priekinės sėdynės
  Front seat temperature adjustable in three stages. Left and right seat can be adjusted separately. The balance of the seat heating between the seat surface and backrest can be adjusted via the PCM.
- ISOFIX tvirtinimo sistema galinėse sėdynėse

Eksterjeras

- Šoninės apdailos
- Išorės veidrodėlių apatinė apdaila ir pagrindas, dažyti juoda (Black) spalva
- Šoninių langų apvadai, sidabrinės (Silver) spalvos
- Durelių rankenėlės dažytos automobilio kėbulo spalva
- Elektra atidaromas bagažinės dangtis
- Pėsčiųjų apsauga

Stogo ir transportavimo sistemos

- Aliumininis stogas
- Paruošimas vilkimo įrangai

Dekoratyviniai lipdukai

- Modelio ženklas, sidabrinės (Silver) spalvos
- Šoninės apdailos juostos, juodos (Lava Black) spalvos su 3D tekstūra The characteristic sideblades of the Macan emphasise the sporty character of the vehicle.

Transmisija / pakaba

- Padidintos talpos baterija "Plus"
  Gross Capacity of 100 kWh*
  *may vary depending on ageing and battery temperature
- „Porsche E-Performance" transmisija su nuolatinio magneto sinchroniniu varikliu (PMSM) priekinėje ir galinėje ašyse
- Vairo stiprintuvas
  Electromechanical power steering with variable steering ratio and steering pulse generator
- Keturių varančiųjų ratų sistema (4WD)
  Four-wheel drive including electronically controlled Porsche Traction Management (ePTM)
- Plieninė spyruoklinė pakaba su aktyvia pakabos valdymo sistema „Porsche Active Suspension Management“ (PASM)
  Electronically controlled active damping system with four manually selectable modes ('Normal', 'Sport', 'Sport Plus*' and 'Offroad').
  * Depends on equipment
- Stabdžių sistema su raudona (Red) spalva dažytomis stabdžių apkabomis
  Braking system with brake calipers in Redó-piston aluminium monobloc fixed-caliper brakes at front with internally vented brake discs (diameter 375 x 36 mm)Single-piston floating calipers at rear with brake discs (diameter 350 x 30 mm)
  FunctionsRegenerative braking systemMulti-collision brakeBrake pad wear monitoringElectrically operated parking brakeAuto-hold functionHill descent control (Porsche Hill Control, PHC)Driving stabilisation system Porsche Stability Management (PSM) with ABS, ASR, ABD, MSR and trailer stabilisation

- 1 pavaros automatinė transmisija

Šviesos ir apšvietimas

- Šviesos diodų (LED) pagrindiniai priekiniai žibintai
  LED main headlights including automatic high beam, dynamic levelling system, four-point LED daytime running lights and LED indicator lights
- Galinė šviesos juosta su „PORSCHE" užrašu
  - LED taillights with three-dimensional lighting graphics and light strip- ‘PORSCHE’ logo in glass look integrated into light strip
- Elektra užlenkiami išoriniai galinio vaizdo veidrodėliai
  Electrically adjustable, foldable and heatable exterior mirrors aspherical on driver‘s side including automatic lowering of the front passenger mirror glass to the parking position when reverse gear is selected
- Rankiniu būdu valdomas, pritemstantis vidinis galinio vaizdo veidrodėlis
- Šilumą sulaikantis priekinis stiklas
- Lietaus jutiklis Two-speed windshield wiper system with intermittent mode including rain sensor and windscreen washer nozzlesHeated rear window with 'auto off' function

Interjero paketai / dekoras

- Interjero apdailos paketas, juodos (Black) itin blizgios (high-gloss) spalvos
  Items in Black (high-gloss): - Front and rear door panel trim strips with decorative inlays
  Items in Black (satin-gloss): - Dashboard trim with decorative inlay
  In conjunction with the front passenger display the dashboard trim on the front passenger side is omitted
- Apdailos elementų paketas, pilkos (Silvershade) spalvos Silvershade accent trim in front and rear doors and dashboard

Saugos diržai / sėdynės

- Saugos diržai - juodos (Black) spalvos
- Galvos atramos
- Trijų taškų saugos diržai su automatiniais įtempėjais priekyje

Vairas / pavarų perjungimo svirtis

- Daugiafunkcis odinis vairas su važiavimo rėžimų perjungimo valdikliu
  - Mode Switch for selecting the drive modes: Normal, Sport, Sport Plus* and Offroad- Predefined drive modes can be customised with various sporty vehicle settings, such as suspension level (note: setting options are equipment-dependent)
  *Sport Plus mode is only available in conjunction with the optional Sport Chrono Package.
- Rankiniu būdu reguliuojama vairo pozicija

Interjeras

- Medžiaginis stogo apmušalas
  Roof lining and A- and B-pillar trims in fabric
- Skydeliai nuo saulės priekyje
- Pedalai iš nerūdijančio plieno
- Durelių slenksčiai iš aliuminio su modelio pavadinimu

Rakteliai, kilimėliai ir įdėklai

- Grindų kilimėliai Priekiniai kilimėliai su išsiuvinėtu „PORSCHE“ užrašu

Pagalbos sistemos

- Automobilio parkavimo sistema „ParkAssist" su vaizdą aplink automobilį fiksuojančia sistema „Surround View"
- Automatinio automobilio parkavimo sistema su 2D Surround View
  Automatic Parking with 2D Surround View offers a range of functions that support and assist the driver:
  HighlightsAutomatic Parking uses ultrasonic sensors and camera systems to automatically detect parking spaces and measure their size. Once the system has signalled that a parking space is large enough, the driver can initiate and control the parking manoeuvre. The system automatically takes over the steering and forward and reverse movement of the vehicle. The Active Parking Support is capable of parking the vehicle in parallel and perpendicular parking spaces.2D Surround View provides the necessary all-round view from every angle when parking and manoeuvring. Four high-resolution cameras on the vehicle provide a 360° view of the surroundings for convenient manoeuvring. In addition, the driver can select individual camera perspectives that offer an even more detailed overview.
  Note: All systems operate within their system limits and require constant monitoring by the driver.
- Kelio ženklų atpažinimo sistema (TSR)
  Traffic sign recognition of speed limits, 'no overtaking' zones (start and end) and various other signs (skid risk, temporary restrictions) in interaction with the vehicle sensor system. Includes a display on the colour screen in the instrument cluster. In the event of sign recognition failure (for example in heavy rain or darkness), the speed limit stored in the navigation module will be displayed
- Eismo juostos keitimo asistentas „Lane Change Assist"
  Alerts the driver to vehicles rapidly approaching from behind or vehicles travelling at the same speed in potential blind spots.

  The warning is emitted by lights in the exterior mirrors.

  The function is activated by the driver using Porsche Communication Management (PCM) and is available from approximately 10 km/h – 250 km/h.

  Below a speed of approximately 30 km/h, Turn Assist (rear) also comes to the driver's aid by monitoring the area to the rear of the vehicle in turning situations

  Rear Cross Traffic Alert
  The Rear Cross Traffic Alert uses the rear radar and, where system limitations allow, warns the driver when reversing slowly of oncoming traffic when the parking aid is activated. The system warns, for example, of critically approaching vehicles when leaving a perpendicular parking space. The information is provided in stages – visually on the PCM screen, audibly and, if necessary, with a jolt of the brakes.

  Exit warning
  The exit warning warns of other vehicles approaching from behind when the door is opened. The system uses the LED lighting in the interior door handle as a warning.

  Note: The functions are subject to system limitations. The driver must monitor at all times and intervene in cases of doubt

Pagalbos sistemos

- Važiavimo juostos kontrolės sistema „Lane Keeping Assist", kartu su avarinio sustojimo funkcija „Emergency Stop"
  Camera-based system for automatic detection of divider line markings on the road. Actively countersteers if your vehicle inadvertently threatens to leave the current lane. System is available from approximately 65 km/h - 250 km/h.
  Emergency Stop function: Brings the vehicle to a halt (subject to system limitations) if the driver fails to respond (for example due to health reasons). If the vehicle detects an absence of driver activity, it uses visual and audible warnings, a brief tightening of the seatbelt and if necessary a jolt of the brakes to attempt to prompt the driver to resume control of the vehicle. Should this be unsuccessful, after a moderate delay the vehicle will come to a halt in the lane, activate the hazard warning lights and trigger a call to the emergency services.
- Sankryžos asistentas (Intersection Assist)
  The Intersection Assist monitors the front of the vehicle to see whether vehicles, pedestrians or cyclists are crossing the road and can reduce the consequences of a collision by issuing a warning or automatically braking within the system limits.
- Adaptyvi pastovaus greičio palaikymo sistema
  Radar-based technology that automatically maintains a specified distance from the vehicle in front by gently braking the vehicle as required, even down to a halt
  Note: The functions are subject to system limitations. The driver must monitor at all times and intervene in cases of doubt
- Perspėjimo ir stabdymo asistentas
  The Warning and Brake Assist system monitors the environment in front of the vehicle. An impending head-on collision with vehicles, pedestrians or cyclists can be detected within the limits of the system when driving at urban and extra-urban speeds. In this case, the system alerts the driver by means of an audible and visual warning, as well as by a braking jolt where appropriate.
  If required, the system can also support driver braking or initiate automatic deceleration to reduce the collision speed or possibly avoid the collision.

  In addition, the following functions are also part of the Warning and Brake Assist system:

  The distance warning can detect if there is a safety hazard due to driving too close to the vehicle in front and warn the driver via the display in the instrument cluster.
- Manevravimo ir posūkio asistentas
  Swerve Assist supports the driver's steering intervention in a collision-critical situation, when the driver wants to avoid an obstacle by performing a steering manoeuvre.

  When turning, the Turn Assist monitors the traffic in the opposite lane as well as pedestrians and cyclists, and can avoid a collision by warning and braking within the limits of the system.
- Avarinio skambučio sistema
- Aktyvus greičio ribojimo asistentas (Active Speed Limit Assist)
  Once activated, the function prevents the set speed from being exceeded. This can be set manually by the driver using the control lever on the steering wheel or automatically by the system based on the detected maximum permitted speed.
- Vairuotojo nuovargio atpažinimo sistema By tracking of driving behaviour, user interaction and view direction of the driver, there will be optical and acoustic warnings if distraction or indications of tiredness are detected.

Komforto ir kasdienės veiklos sistemos

- 2 zonų automatinė klimato kontrolės sistema
  2-zone automatic climate control with separate temperature settings for driver and front passenger, automatic air-recirculation mode including air quality sensor and separate air volume control for driver and front passenger as well as rear passengers (left / right), AC-MAX button and humidity sensor- Air conditioning control via black panel with real glass surface and monochrome 4.4-inch display- Parking pre-climatisation including pre-conditioning of the battery
- Aktyviosios anglies salono oro filtras
  Fine dust filter PM2.5 including anti-allergen coating, predictive air circulation control for tunnels and cyclical fresh air supply
- Apsupančio salono apšvietimo paketas (Ambient)
  Ambient and communication lightingAmbient lighting with thirty selectable coloured light designs in the following components:rising center consolefront and rear door panelsstorage compartment of the doorsin the front footwellfront cup holders
  Communication light to reinforce notices, warnings and support status information.56 LEDs in the dashboard and the door panels give the driver functional feedback in the peripheral vision so that he can react even faster.The following functions are displayed:ambient lightingwelcome/leavingLaunch Controlcharge statusVoice Pilotexit warningdrive mode changenavigationtakeover requestalarm
  Interior lightingglove compartmentreading spot lights for driver and front passengerreading lights rear left and rightluggage compartment
- Signalizacija kartu su vidaus stebėjimu
- Nerūkantiesiems skirtas paketas
- Gamyklinis paruošimas alkobloko sistemai
- Šoninės ir centrinės oro pagalvės priekyje
- Oro saugos pagalvės
  Full-size airbags for driver and front passengerCurtain airbags along entire roof frame and side glazing from the A-pillar to the C-pillarRollover detection for activation of curtain airbags and seat belt pretensioners
- Beraktė automobilio užvedimo sistema „Keyless Drive“
- Avarinio perspėjimo ženklas
- Vairuotojo sėdynės atminties paketas Memory function for driver's seat and exterior mirror adjustment

PORSCHE

Audio / Komunikacija

- Įrangos paketas „Sound Package Plus"
  Garsų paketas "Sound Package Plus" užtikrina galingą ir dinamišką garsą visose sėdynėse.
  Detaliau:10 garsiakalbiųlš viso 150 vatų
- Mobiliojo telefono dėtuvė su belaidžio krovimo funkcija (iki 25W)
  Wireless chargingSmartphone storage compartment in the centre console including wireless charging with up to 25W (Wireless charging requires a compatible mobile device. Actual charging power may vary.)
  Power outlets in the passenger compartment1 socket (12 volt) at the front in the centre console2 USB-C Power Delivery connectivity and fast charging interfaces in the front storage compartment2 USB-C Power Delivery fast charging interfaces on the rear centre console
- Skaitmeninis radijo imtuvas (DAB)
  In addition to analogue stations, enables reception of digital radio broadcasts in the DAB+ and DMB Audio formats, offering far superior sound. DAB twin tuner permanently scans for alternative reception frequencies for the current station with simultaneous refreshing of station list.
  Note: Reception dependent upon local digital station availability
- 12,6 colių skaitmeninis prietaisų skydelis, 10,9 colių jutiklinis centrinis ekranas Instrument cluster12.6-inch curved display
  Central display10.9-inch touchscreen display
  Smartphone integrationApple® CarPlay with Siri® voice recognition - to use the apps of your iPhone® even when you're on the moveAndroid Auto - to use the apps of your Android phone even when you're on the move

E-mobilumas

- Akustinis važiuojančio elektromobilio perspėjimo garsas (AVAS)
  The legally required acoustic vehicle warning system is always active. An emotive vehicle sound that was developed by Porsche engineers to increase road safety.
- Šilumos siurblys
  The heat pump uses the residual heat of the drivetrain or the ambient heat to efficiently warm up the vehicle interior. With outside temperatures below 20 °Celsius and activated air conditioning, the heat pump helps to save energy and has a positive effect on the range.
- AC lizdas palaikantis iki 11 kW įkrovimo galią
- Įkrovimo kabelis, skirtas įkrovimui iki 11 kW (6 m. ilgio)
- Rankiniu būdu atidaromas įkrovimo lizdo dangtelis Manually opening charge ports with button for unlocking the charge plug on driver and passenger side

Porsche Connect paslaugos

- Porsche Connect paslaugų paketas Enhance the digital experience in your Porsche with Porsche Connect. Porsche Connect can be booked free of charge for 10 years when purchasing a Connect-enabled new vehicle. Term: monthly, notice period: one month. Entertainment Enjoy a wide range of entertainment and download your favorite local apps from the App Center. The App Center gives you access to popular apps from Porsche and third-party providers that have been optimised for vehicle use. Benefit from convenient transfer of your smartphone content via Apple® CarPlay or Android Auto. Market-specific data volume for the use of the App Center, Connected Media and the Wi-Fi hotspot is provided free of charge for 4 years from activation (via data pass with limited data volume/data speed from country-specific contract partners). Digital Assistant With the AI-supported Voice Pilot you can control the navigation, supported apps and other vehicle functions by voice command. Navigation Optimize your route and travel time with the help of real-time traffic information. The Charging Planner efficiently integrates your charging stops, taking into account the current state of charge and available charging stations. My Porsche App Remotely manage your Porsche conveniently via the My Porsche app on your smartphone. The Porsche Digital Key turns the iPhone, Apple Watch or any compatible Android™ device into your digital vehicle key that can be shared with up to 7 other people. To be able to use the My Porsche app, your smartphone must have at least iOS 16.0 or Android 8.0. Precondition Porsche Digital Key: Pre-configuration of the comfort access (4E6). General information on compatibility and use can be found on the Porsche Digital Key information page. Smart Support Services The emergency call system supports the driver in case of an accident, transmitting personal and vehicle-related data to the emergency call center. The service is automatically active for 10 years from delivery. The integrated hardware supports 4G/5G NSA (non-standalone) technology. Insofar as services require connectivity via the integrated hardware, the availability of a 4G/5G NSA network is a prerequisite for their functioning. Further information on the different services, free inclusive periods and follow-up costs can be found at www.connect-store.porsche.com, in the Owner's Manual or from your Porsche partner. Some or all Porsche Connect services may not be available in certain countries.

Valdymo kodai

- Juodos (Black) spalvos interjeras
- Vairo apdailos paketas be dekoratyvinio siuvinėjimo
- Be vairuojamų galinių ratų

Kiti

- Juodos (Black) spalvos padangų slėgio jutikliai

Svarbi informacija

Šiame dokumente pateiktos standartinės specifikacijos atitinką europinį bazinį modelį ir neapima konkrečios šalies specifinės įrangos. Norėdami gauti daugiau informacijos apie prieinamumą, tikslias įrangos specifikacijas, emisijas ir homologacijos standartus, kreipkitės į "Porsche" centrą.

PORSCHE

Papildoma įranga

Užsakymo numeris	Modelio metai	Automobilis
XABDC1	2027	Macan 4S

Įranga

Kategorija	Kodas	Aprašymas
Kėbulo spalva	U4	Žalia (Aventurine Green Metallic)
Dekoratyviniai lipdukai	0NA	Nuimtas modelio ženklas
Ratlankiai	54R	21 colio „Macan Design" ratlankiai
Ratlankių aksesuarai	1G8	Padangų sandarinimo mišinys ir elektrinis oro kompresorius
Sėdynės	4D3	Vėdinamos priekinės sėdynės
Įrangos paketai	PB1	Praplėstos apimties, pažangios įrangos paketas „Advanced“
Eksterjero paketai	2D1	„SportDesign" kėbulo apdailos paketas Porsche Exclusive Manufaktur
Eksterjeras	6H1	Šoninės apsauginės juostos dažytos automobilio kėbulo spalva
	QJ4	Šoninių langų apvadai, juodos (Black) itin blizgios (high-gloss) spalvos Porsche Exclusive Manufaktur
Transmisija / pakaba	8LE	Kompasas prietaisų skydelyje
	G1Z	1 pavaros automatinė transmisija
Šviesos ir apšvietimas	4GR	Šildomas priekinis stiklas
	VW6	Šilumą ir triukšmą sulaikantys stiklai, kartu su tonuotais galiniais stiklais
Saugos diržai / sėdynės	3J7	Priekinių sėdynių galvos atramos su įspausta „Porsche“ emblema Porsche Exclusive Manufaktur

Porsche kodas: http://www.porsche-code.com/PVHZVCT3

Įranga

Kategorija	Kodas	Aprašymas
Vairas / pavarų perjungimo svirtis	2FJ	GT šildomas sportinis vairas aptrauktas oda
Pagalbos sistemos	KS5	Papildytos realybės Head-up ekranas
	PX9	Nuotoliniu būdu valdoma automobilio parkavimo sistema „Remote ParkAssist" kartu su vaizdą aplink automobilį fiksuojančia sistema „3D Surround View" ir Porsche skaitmeniniu raktu (Porsche Digital Key)
	GJ7	Porsche „Drive Assist" sistema
Komforto ir kasdienės veiklos sistemos	6C4	Šoninės oro saugos pagalvės gale

Svarbi informacija

Šiame dokumente pateiktos standartinės specifikacijos atitinką europinį bazinį modelį ir neapima konkrečios šalies specifinės įrangos. Norėdami gauti daugiau informacijos apie prieinamumą, tikslias įrangos specifikacijas, emisijas ir homologacijos standartus, kreipkitės į "Porsche" centrą.„Porsche" pasilieka teisę be išankstinio įspėjimo keisti specifikaciją, pristatymo paketą, pratęsimo laiką ir kainą bei kitą informaciją apie gaminį. Spalvos ir medžiagos gali skirtis nuo nurodytų.

Porsche kodas: http://www.porsche-code.com/PVHZVCT3